

**Wet and Dry
Application**

**Air Driven type,
No Electric Operation**

AQUA
SYSTEM CO.,LTD.

Air Vacuum Cleaner for 18 liters can

Simple Structure and Little Trouble



**Without regular parts replacement, you can use it for a long time.
As no electricity required, this product is possible for immerse washing.
No filter is necessary to suck materials (larger than 1mm)**



Application

- **Cleaning at and around machines & vehicles placed in maintenance facility.**
- **Recommendable to suck the materials in the factories for Printing Paper-making, Plastic, Rubber product manufacturing etc.**
- **Cleaning at ship-yards, warehouses or passageways etc.**
- **Cleaning septic tanks, Sucking sludge and waste water from welding process.**



Easy for operation

**Just connect air compressor and place it on 18L can.
Garbage easily to be categorized by changing the cans.**



Specifications Table

Model	APPQ0550S-i	APPQ0550-i
Acceptable Viscosity	3,000cP	
Sucking Capacity	80 (L/min)	
Max. Discharge Head	2m	
Body	Aluminum	
Packing	NBR (Fluorine)	
Hose	PVC	
Compressor (Hp)	5	
Compressor Air (Mpa)	0.4~0.6	
Noise (dB)	90	
Weight (kg)	4.5	5.2
Automatic Stopper	-	★
Filter	-	★

“★” mark means “included.”



The Video to show
how it works

Image (18 liter can is separately sold.)

Air Vacuum Cleaner

**Air Type Industrial Application,
Simple Structure + Attractive Price**



Model : APPQ0550S-i

- Sucking the liquid, even mixed with the foreign materials, is possible.
- Collecting foreign materials on the surface of water.
- Remarkable high sucking power.
- Using for open 18L can, just place on it.
- Due to air driven operation, no electricity is required. The possibility of explosion from igniting flammables or combustibles is almost "zero".
- Sucking with air
- More economical and a longer service time than electric type cleaner.
- Sucking sludge is possible.

**About 35% less
than Model APPQ0550-i**

Accessory (Several options are available)

1. APPQ0550 (400) S-i body
2. Suction PVC hose 2m
3. Suction Nozzle (Only Round Nozzle)



Image

※18L can are not included.



Backside of APPQ0550S-i

※Filter and auto-stopper are not included, to be separately sold.



Filter Set



Automatic stopper

Specifications Table

Model	Acceptable Liquid	Max. Viscosity	Max. Delivery Rate	Max Discharge Head	Materials			Compressor	Noise (dB)	Weight
					Body Nozzle	Packing	Hose			
APPQ0550S-i	Oil	Up to 3,000cP	80 (L/min)	2 (m)	Aluminum	NBR	PVC (2m · ϕ 32)	Higher than 5HP	90	4.2 (kg)

AQUASYSTEM Co.,Ltd, JAPAN

1-3-1 Kyo-machi, Hikone-shi, Shiga, Japan

TEL: +81-749-23-9139 FAX: +81-749-23-9122

HP: <http://en.aqsys.co.jp> E-mail: trade@aqsys.co.jp

Alibaba Shop: <https://aquasystem.trustpass.alibaba.com/>

Sales: