



Maximum cooling capability



Safe air-driven type meeting SDGs

Safe use in the fire prohibited area with non-electric air-driven mister. It also has a water-saving function.

Dedicated bottle becomes a simplified tank

1 \ell water is for about 8 hours operation by adjusting the valve opening.

*Available for bottles other than dedicated bottle (e.g. 10 \mathcal{\ell} tank)



Industry's First Full Air-Driven Cool Mister



Mountable to various types of factory fan according to the site and use

The most suitable for heat stroke measures in a hot area



For the electrostatic measures in the chemicals factory



For comfortable work in the fire prohibited area!

Mist system available by mounting on your factory fans and blowers which is not connecting directly to the water supply.

Characteristics

- Cool ventilate and blow over the wide area with circulator and oscillating function.
- · Mist and air quantity is adjustable with valve.





Product Specification

Nozzle type	Binary fluid
Mist spray quantity	Adjustable
Water feed method	Tank, dedicated bottle
Weight (kg)	1.0

Mountable Products

*Performance varies according to the air pressure and piping condition.

Oilless stand type factory fan AFG-18NL/AFG-24NL

Not necessary to lubricate!
Non-oil-supply air motor is adopted!



Oilless floor type factory fan AFF-18NL

Smooth movement with caster! To ventilate the stuffy air.

Floor type

Pneumatic



Oilless wall type factory fan **AFK-18NL**

Install on the wall and pole to use the space effectively!

Wall type





AFK-18NL

AQUASYSTEM CO.,LTD.

TEL 81-749-23-9139 http://en.aqsys.co.jp/ FAX 81-749-28-1474 mail trade@agsys.co.jp

1-3-1, Kyo-machi, Hikone-city, Shiga, 522-0081, Japan name: FL-2023-04

2023.04 AZZZ F