

Electric drum pump used for kerosene, light oil Equipped flowmeter Being distributed



Control the amount of solution pumped out Maximum cost savings!



Kerosene, light oil

Electric 100V



Can be seen from afar !
Type of large meter TDP-M33

Can check usage traffic !
Type of hand gauge TDP-MN


Simple turbine Flowmeter
(liquid crystal digital display)
TB-K24-FM

The pump is neatly integrated !
Standard gauge type TDP-M


- Speciality 1** Control the amount of solution pumped out, so there is no waste
- Speciality 2** High efficiency pump, pumping a drum in about 7 minutes
- Speciality 3** Convenient for subdividing and supplying oil to agricultural machinery

Parameter table

Product code	TDP-M	TDP-MN	TDP-M33	TDP
Current (V)	100			
Electricity (A)	2			
Rated (minutes)	Can work continuously			
Discharge pressure (Mpa)	0.04			
Maximum discharge (1CP/L/min)	30			
Maximum lift (m)	4			
Maximum suction capacity (m)	2			
Accessory	Hose	Oil resistant hose (2m×φ20)		
	Nozzle	Hand pump nozzle (GN-AL20)		
	Flowmeter	Digital type (road part)	Digital type (pump part)	Mechanical machine
Electricity wire (m)	2			
Weight (kg)	5.2	6.7	5.5	4.8



Subdivision work can also be done quickly.



Refueling agricultural machinery is very simple

Other TDP types

Just by integrating the flowmeter and having an easy-to-use performance, but also has high cost performance and is favored by many customers. Easy to use.

	TDP-M	Company A	Company B
Flowmeter	○	×	×
Discharge amount	○	◎	△
Continuous operation	◎	△	△
Reliability	◎	◎	×
Cost performance	◎	△	○



※Pump without flowmeter (TDP) is also available.

Electric type Easy to use

**Pumps in long distances
Auto shut off when full**

Portable electric pump
EVP Series

Electric type

Kerosene, light oil



Pump head
EVP56-100



Type of hose line equipment
EVPH56-100

Speciality

- [1] Can be equipped with flowmeter and automatic stop nozzle
- [2] Built-in drain valve
- [3] The current can be changed to 200V

Used for drums
EVPD56-100

**Not only for kerosene or light oil
But also be used with low viscosity oils**

Portable electric pump
EMH Series

Electric type

Kerosene, light oil, Oil



Viscosity less than 500cP



Pump head
EMH-20FC



Type of hose line equipment
EMHH-20FC

Speciality

- [1] Can be used with all types of containers
- [2] Vane pump with integrated drain valve
- [3] Equipped with a thermal protector

Used for drums
EMHD-20FC

Compressed air type Safe and secure even in fire-prohibited areas

**Avoid leaving the solution in the container
When you want to use in areas where fire is strictly prohibited**

Pneumatic vacuum pump
APD-20(25)G

Compressed air type

Kerosene, light oil



Air Compressor
1 HP

Viscosity less than 3000cP



APD-20(25)GN



Safety valve



Pressure gauge

Speciality

- [1] Less liquid left (about 200cc), no waste
- [2] Safe pumping of volatile and flammable liquids
- [3] Be safety with regulator and safety valve

APD-20(25)G

**Low - Medium - High
Choose the right viscosity**

Pneumatic portable pump
ACH · AMVH · AMH1 Series

Compressed air type

Kerosene, light oil, Oil
(AMVH · AMH1)



Self-priming type



Air Compressor
5 HP

Viscosity less than 5cP

Used for drums
ACHD-20AL

Head part
ACH-20AL



Air Compressor
5 HP

Viscosity less than 1500cP

Used for drums
AMVHD-20FC

Head part
AMVH-20FC



Air Compressor
3 HP

Viscosity less than 2000cP

Used for drums
AMH1D-20FC

Head part
AMH1-20FC

Speciality

- [1] Because it is a pneumatic motor, there is no need to worry about electric leakage
- [2] Use for drums, locomotives or full types are available
- [3] Can choose to pump according to the solution, viscosity or height when pumping

※Make sure to use an air filter/lubricant

Parameter table

Product code	EVP56-100	EVPD56-100	EVPD-56ATN	EVPD-56K24	EVPD-56K24ATN	EMH-20SUS	EMHD-20FC
Permissible container	Head part		200L drum with tight lid				
Permissible Viscosity (cP)	Kerosene, light oil					500	
Current - Voltage	100V 5.5A					100V 0.9A	
Pumping capacity (1cP/L/min)	46	20	35	20	30		
Maximum lift (m)	10						
Maximum suction capacity (m)	2					5	
Accessory	Hose	G1 Female	Coupling, Heat resistant rubber hose			Rc3/4	Heat resistant rubber
	Nozzle	-	Hand nozzle	Auto-stop nozzle	Measuring nozzle	Auto-stop nozzle	Rc3/4
	Flowmeter	-					O
Electricity wire (m)	2					3	
Weight (kg)	7.4	12	13.4	12.4	14.4	8.8	11.8

Product code	APD-20G (N)	APD-25G (N)	ACH-20AL	AMVH-20FC	AMH1-20FC	ACHD-20AL	AMVHD-20FC	AMH1D-20FC
Permissible container	200L drum with tight lid		Head part		200L drum with tight lid			
Engine type	Compressed air pressure		Propeller engine		Radial piston engine		Propeller engine	
Pump type	Sealed pressurization		Centrifugal pump	Vane pump		Centrifugal pump	Vane pump	
Permissible Viscosity (cP)	3,000		5	1,500	2,000	5	1,500	2,000
Air consumption (L/min)	-		508	560	415	508	560	415
Pumping capacity (1cP/L/min)	55 (50)	115 (70)	50	45	32	50	45	32
Maximum lift (m)	2		5	10	15	5	10	15
Maximum suction capacity (m)	-		2	5		2	5	
Accessory	Suck	Heat resistant rubber		Rc3/4		Equipped with Coupling, Heat-resistant rubber hose, Ball Valve faucet		
	Discharge	Ball Valve (Manual Pump Faucet)		Rc3/4		Include camlocks, Oil resistant PVC hose, suction pipe, Strainer Filter Set Included		
Weight (kg)	6.4(6.3)	8.8(8.3)	4.5	7.8	8	10.7	14	13.4

※Depending on the needs, accessories will be installed such as pump nozzles or flowmeters.

AQUA SYSTEM CO.,LTD.

TEL +81-749-30-9126 <http://en.aqsys.co.jp/>
 FAX +81-749-23-9122 mailtrade@aqsys.co.jp

1-3-1, Kyo-machi, Hikone-city, Shiga, 522-0081, Japan name : FL-2020-03
 2020.04 CZZZ [B]